

<p>standard type male</p> <p>Bend protection sleeve for cable Ø 5.00mm standard, others on request.</p>	<p>front views</p>
<p>standard type female</p> <p>Bend protection sleeve for cable Ø 5.00mm standard, others on request.</p>	<p>front views</p>
<p>„Quick Lock“ type male</p> <p>Bend protection sleeve for cable Ø 6.50mm standard, others on request</p>	<p>front views</p>

Any cable assembly available on request.

Connectors at both ends as well as cable length and quality as per your specification possible.

Please contact the nearest E-tec sales office or Distributor.

SPECIFICATIONS

Current rating	1 A max. at 100 V AC or 2 A max. at 12 V DC	Withstanding voltage	250 V AC for 1 min.	Insulator material (RoHS compliant)	Nylon UL 94 V-0
Insulator resistance	50 MΩ min. at 250 V DC	Operating temperature	-55°C to +85°C	Insertion force	4.5kg max.
Contact resistance	30 mΩ max.	Contact material (RoHS compliant)	Brass	Extraction force	0.8kg min.
		Contact plating	Silver; MQ Type = Gold	Insertion/extraction cycles	500 min.

Ordering Code

MDP - xxx - XX 01 - xx

<p>Nbr of contacts</p> <p>003 to 008</p>	<p>Types</p> <p>MA = male standard FA = female standard MQ = male „Quick Lock“</p>	<p>Plating</p> <p>MA & FA Type: AGZ = silver MQ Type only: 55 = gold</p>
--	--	--